

## TRAILER - SINGLE TEMPERATURE



### A-500

When your cargo deserves the best of the best

**UNIT** Width 2076 mm x Depth 440 mm x Height 2270 mm

- Electronically governed NRMM compliant 4-speed engine
- Fuel consumption monitoring
- Most accurate temperature control in the market
- Fastest pulldown
- Fully variable airflow independent of unit engine speed
- Quietest high-capacity unit in the Market

#### PERFORMANCE

##### REFRIGERATION CAPACITY

SYSTEM NET COOLING CAPACITY UNDER A.T.P. CONDITIONS AT 30 °C AMBIENT

Capacity on engine power 0°C	19500 W
Capacity on engine power -20°C	10400 W
Capacity on electrical stand by 0°C	14600 W
Capacity on electrical stand by -20°C	8400 W

##### AIRFLOW: INDEPENDENT FROM UNIT ENGINE SPEED

Airflow volume @ 0 Pa static pressure - Default @ Pull Down	5500 m3/hr
Airflow volume @ 0 Pa static pressure - Max @ Pull Down	6000 m3/hr
Airflow volume @ 0 Pa static pressure - Default @ Set Point	3400 m3/hr
Airflow volume @ 0 Pa static pressure - Max @ Set Point	5500 m3/hr

#### TECHNICAL DATA

##### HEATING CAPACITY: BOX TEMPERATURE +2 °C

Capacity on engine power (Outside air temperature: -20°C)	15900 W
---	---------

##### WEIGHT

INCLUDING BATTERY

Model Standard	835 kg
----------------	--------

##### ENGINE

Maintenance Interval	3000 hrs
Number of cylinders	4
Displacement	2,1

##### ELECTRICAL STAND BY MOTOR

Voltage / Phase / Frequency	400/3/50 460/3/60
Rating	9.3 kW

##### SOUND PRESSURE LEVEL

High Speed Diesel	67 dB(A)
Electric Standby	64 dB(A)

## TRAILER - SINGLE TEMPERATURE

	STANDARD FEATURE	OPTION FACTORY FITTED	OPTION DEALER FITTED
<b>LIFE COST MANAGEMENT</b>			
Fuel consumption monitoring	x		
Fuel level sensor		x	x
Fuel filtration and priming system		x	x
Premium AGM battery	x		
2-year warranty coverage	x		
EMI 3000: Extended maintenance interval	x		
<b>DATA CAPTURE &amp; COMMUNICATIONS</b>			
TrackKing - 2 Years Contract	x		
Trailer Assist EBS Harness		x	x
ServiceLog maintenance logger	x		
ComplianceLog data logger	x		
TouchLog independent data logger		x	x
Wintrac (data analysis software)			x
USB data port	x		
<b>LOAD PROTECTION</b>			
Adjustable airflow	x		
Air Straightener (from Q4 2020)		x	x
Air Chute (from Q4 2020)		x	x
Discharge Air Control Freeze protection	x		
OptiSet Plus pre-set operating parameters (from Q4 2020)	x		
Door switches		x	x
Diesel/Electric Auto Switching + Auto Phase Correction	x		
<b>CUSTOMIZATION</b>			
Whisper quiet operation	x		
Solar Panel		x	x
Tail lift battery charger (from Q4 2020)		x	x
Fuel Tank (Plastic 230L or Aluminium 190L)		x	x
Secured 3rd Party accessories power connection (from Q4 2020)	x		
<b>EASE OF USE</b>			
Proactive alarm notifications	x		
Triple Combo Display (Fuel, Alarms, Temperature indications)		x	x