SELF POWERED TRUCK - SINGLE TEMPERATURE



UNIT Width 1887 mm x Depth 919 mm x Height 688 mm
CONDENSER Width 1887 mm x Depth 919 mm x Height 688 (Whisper option 704)
mm

T-1000R

Delivering what matters

- · Quiet operation
- · Low fuel consumption
- · Low life cycle costs
- $\boldsymbol{\cdot}$ Easy to use and service
- · Reduced emissions and waste

PERFORMANCE						
REFRIGERATION CAPACITY SYSTEM NET COOLING CAPACITY UNDER A.T.P. CO	NDITIONS AT 30 °C AMBIENT	AIRFLOW ON HIGH SPEED ENGINE OPERATION				
Capacity on engine power 0°C	10000 W	Airflow volume @ 0 pa static pressure	3200 m3/hr			
Capacity on engine power -20°C	5400 W	Discharge velocity - airthrow	6.2 m/sec			
Capacity on electrical stand by 0°C	7100 W					
Capacity on electrical stand by -20°C	4100 W					

TECHNICAL DATA						
COMPRESSOR		REFRIGERANT CHARGE				
Model	X426 C5	Charge	3.4 kg			
GENERIC (BOXLENGTH, REFRIGERANT,)		WEIGHT INCLUDING BATTERY				
Boxlength	7.5 - 8.5 m	Model 30	457 (Whisper option +17) kg			
Refrigerant	R-452A	Model 50	514 (Whisper option +17) kg			
Airflow	3200 m3/hr					
Controller	Truck Smart Reefer 3					
ENGINE		ELECTRICAL STAND BY MOTOR				
Model	TK 376	Voltage / Phase / Frequency	400 / 3 / 50 230 / 3 / 50 230 / 3 / 60			
Rating	14.6 kW					
Maintenance Interval	2000 hrs	Rating	7.5 kW			
no. of cylinders/displacement	TK 376 / 3 / 1115 cm3					

SELF POWERED TRUCK - SINGLE TEMPERATURE

	STANDARD FEATURE	OPTION FACTORY FITTED	OPTION DEALER FITTED
LIFE COST MANAGEMENT			
ThermoKare Service contracts			x
Cycle-Sentry start/stop control system	х		
EMI 2000 extended maintenance	x		
Fuel level sensor		х	X
Thermo King high performance battery	x		
Thermo King Energy battery		х	
Premium AGM battery		х	
2-year warranty coverage	х		
DATA CAPTURE & COMMUNICATIONS			
TouchPrint data capture			X
TouchPrint Printer			х
ServiceWatch maintenance logger	x		
DAS (Data Acquisition System)		х	
TracKing? (tracking and load monitoring)			X
Wintrac (data analysis software)			х
LOAD PROTECTION			
TSR-3 standard in-cab display	x		
Heater Bar Kit		х	x
Auto phase correction	x		
SafeGuard battery protection kit		x	Х
Door switches		х	x
Diesel/electric auto switching	х		
CUSTOMIZATION			
TSR-3 premium in-cab display		x	
Whisper noise attenuating kit		x	
TSR-3 rear remote control		x	
Electronic Fuel Capture			х
Remote Status Light and Combination Display			x
Hose management kit		х	
Solar Panel			x
Body mount enclosure			x
90L fuel tank		х	х
Triple Combo Display			X