

SELF POWERED TRUCK - SINGLE TEMPERATURE

T-560R



Enhanced self-powered refrigeration unit for small & medium sized trucks

UNIT Width 1676 mm x Depth 926 mm x Height 596 mm
CONDENSER Width 1676 mm x Depth 926 mm x Height 596 mm

- Proven performance up to 55 °C
- As tough as the conditions it works in
- Full Thermo King service and parts support
- Ease of use for error-proof operation
- Market leading performance and economy
- Reduced environmental impact
- Frozen, chill or fresh cargo up to 5.5m body
- Stylish new appearance
- Refrigerant: Standard: R-452A / Optional: R-134a

PERFORMANCE

REFRIGERATION CAPACITY SYSTEM NET COOLING CAPACITY UNDER A.T.P. CONDITIONS AT 30 °C AMBIENT		AIRFLOW ON HIGH SPEED ENGINE OPERATION	
Capacity on engine power 0°C	6600 W	Airflow volume @ 0 pa static pressure	2150 m3/hr
Capacity on engine power -20°C	3500 W	Discharge velocity - airthrow	5.5 m/sec
Capacity on electrical stand by 0°C	4800 W		
Capacity on electrical stand by -20°C	2500 W		

TECHNICAL DATA

COMPRESSOR		REFRIGERANT CHARGE	
Model	X214 Deep Sump	Charge	2.5 kg
Displacement	228 cm3		
GENERIC (BOXLENGTH, REFRIGERANT, ...)		WEIGHT INCLUDING BATTERY	
Boxlength	4.0 - 5.5 m	Model 30	370 (Whisper option +17) kg
Refrigerant	R-452A	Model 50	400 (Whisper option +17) kg
Airflow	2150 m3/hr		
Controller	Truck Smart Reefer 3		
ENGINE		ELECTRICAL STAND BY MOTOR	
Model	TK 270	Voltage / Phase / Frequency	400 / 3 / 50 -- 230 / 3 / 50 -- 230 / 3 / 60
Rating	7.5 kW	Rating	4.5 kW
Maintenance Interval	1000 hrs		
no. of cylinders/displacement	TK 270V / 2 / 570 cm3		

SELF POWERED TRUCK - SINGLE TEMPERATURE

	STANDARD FEATURE	OPTION FACTORY FITTED	OPTION DEALER FITTED
LIFE COST MANAGEMENT			
ThermoKare Service contracts			x
Cycle-Sentry start/stop control system	x		
EMI 2000 extended maintenance	x		
Thermo King high performance battery	x		
Thermo King Energy battery		x	
Premium AGM battery		x	
2-year warranty coverage	x		
DATA CAPTURE & COMMUNICATIONS			
TouchPrint data capture			x
TouchPrint Printer			x
Remote Watch	x		
TSR standard in-cab display	x		
LOAD PROTECTION			
Heater Bar Kit			x
Auto phase correction	x		
SafeGuard battery protection kit		x	x
Password protected controller	x		
Door switches		x	x
Diesel/electric auto switching	x		
CUSTOMIZATION			
Whisper noise attenuating kit		x	
Hose management kit		x	
TSR rear remote control		x	
Solar Panel			x
Whisper low noise kit		x	
Body mount enclosure			x
90L fuel tank		x	x
Triple Combo Display			x